

Supplemental Labeling



Dow AgroSciences LLC

9330 Zionsville Road

Indianapolis, IN 46268-1054 USA

Tordon* 22K

EPA Reg. No. 62719-6

Revised Equipment Requirements for Aerial Application

ATTENTION

- It is a violation of Federal law to use this product in a manner inconsistent with its labeling.
- This labeling must be in the possession of the user at the time of application.
- Read the label affixed to the container for Tordon 22K before applying. Carefully follow all precautionary statements and applicable use directions.
- Except as described in this supplemental labeling, use of Tordon 22K is subject to all use precautions and limitations imposed by the label affixed to the product container.

Directions for Use

The current drift management requirements in label for Tordon 22K specify the following: The distance of the outer most operating nozzles on the boom must not exceed 3/4 the length of the wingspan or rotor.

Under this supplemental labeling, this requirement for Tordon 22K has been revised to allow the following: For aerial applications, the boom width must not exceed 75% of the wingspan or 90% of the rotor width.

All other equipment and spray drift requirements remain as specified in the label booklet for Tordon 22K.

*Trademark of Dow AgroSciences LLC

EPA-accepted: 06-10-2003

Revisions: Modifies aerial boom width specifications to be consistent with EPA's draft PR Notice on spray and dust drift label statements.