## SAFETY DATA SHEET



#### 1. Identification

Product identifier R-56
Other means of identification None.

Recommended use Ag Product - Adjuvant

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name Wilbur-Ellis Company LLC
Address 16300 Christensen Rd. Ste 135

Tukwila, WA 98188

**United States** 

**Telephone** Branded Products Information (800) 500-1698

**E-mail** SDS@wilburellis.com

Emergency phone number Chemtrec - Domestic (800) 424-9300 Chemtrec - International +1 703-741-5970

2. Hazard(s) identification

Physical hazardsFlammable liquidsCategory 3Health hazardsSkin corrosion/irritationCategory 2

Serious eye damage/eye irritation Category 1
Carcinogenicity Category 2

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Flammable liquid and vapor. Causes skin irritation. Causes serious eye damage. Suspected of

causing cancer.

**Precautionary statement** 

**Prevention** Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Keep away from heat, sparks, open flames, and hot surfaces. - No smoking.

Keep container tightly closed. Ground/bond container and receiving equipment. Use

explosion-proof electrical, ventilating, lighting, and process equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wash thoroughly after handling.

Wear protective gloves, protective clothing, eye protection, and face protection.

Response IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin with water. If in

eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor. Specific treatment (see this label). If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse. In case of fire: Use appropriate media as described in Section 5 for extinction.

Storage Store in a well-ventilated place. Keep cool. Store locked up.

**Disposal** Dispose of contents and container in accordance with government regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

Material name: R-56 SDS US

1175 Version #: 02 Revision date: 09-26-2017 Issue date: 02-23-2016

### 3. Composition/information on ingredients

#### **Mixtures**

Chemical name	Common name and synonyms	CAS number	%
Proprietary Surfactant Blend Component 1		Proprietary	30 - < 40
Proprietary Surfactant Blend Component 2		Proprietary	20 - < 30
Proprietary Surfactant Blend Component 3		Proprietary	20 - < 30
Solvent Naphtha (Petroleum), Heavy Aromatic		64742-94-5	5 - < 10
Solvent Naphtha (Petroleum), Light Aromatic		64742-95-6	5 - < 10
1,2,4-Trimethylbenzene		95-63-6	1 - < 3
Other components below reportable	levels		< 0.2

Percentage ranges of composition to protect confidentiality or due to batch variation.

#### 4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Take off immediately all contaminated clothing. Rinse skin with water. If skin irritation occurs: Get

medical attention. Wash contaminated clothing before reuse.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact

present and easy to do. Continue rinsing. Get medical attention immediately.

Ingestion Rinse mouth. Get medical attention if symptoms occur.

and pain.

Most important symptoms/effects, acute and

delayed

Indication of immediate medical attention and special

treatment needed

General information

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred

vision. Permanent eye damage including blindness could result. Skin irritation. May cause redness

Take off all contaminated clothing immediately. IF exposed or concerned: Get medical attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

### 5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Specific hazards arising from the chemical

Special protective equipment

and precautions for firefighters

Fire fighting equipment/instructions

Specific methods General fire hazards

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

Use standard firefighting procedures and consider the hazards of other involved materials.

## Flammable liquid and vapor.

#### Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Material name: R-56 SDS US

# Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Take precautionary measures against static discharge. Use only non-sparking tools. Keep combustibles (wood, paper, oil, etc.) away from spilled material.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.

### **Environmental precautions**

## 7. Handling and storage

## Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not get this material in contact with eyes. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

# Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

## 8. Exposure controls/personal protection

#### Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Con	•		
Components	Туре	Value	
Solvent Naphtha (Petroleum), Heavy Aromatic (CAS 64742-94-5)	PEL	400 mg/m3	
,		100 ppm	
Solvent Naphtha (Petroleum), Light Aromatic (CAS 64742-95-6)	PEL	400 mg/m3	
(6.15 6.1.12 66 6)		100 ppm	
US. ACGIH Threshold Limit Values			
Components	Туре	Value	Form
1,2,4-Trimethylbenzene (CAS 95-63-6)	TWA	25 ppm	
Solvent Naphtha (Petroleum), Heavy Aromatic (CAS 64742-94-5)	TWA	200 mg/m3	Non-aerosol.
<b>US. NIOSH: Pocket Guide to Chemical</b>	Hazards		
Components	Туре	Value	
1,2,4-Trimethylbenzene (CAS 95-63-6)	TWA	125 mg/m3	
(		25 ppm	
Solvent Naphtha (Petroleum), Light Aromatic (CAS 64742-95-6)	TWA	400 mg/m3	
(5.12.511.12.00.0)		100 ppm	

**Biological limit values** No biological exposure limits noted for the ingredient(s).

Material name: R-56 SDS US

#### **Exposure guidelines**

#### **US ACGIH Threshold Limit Values: Skin designation**

Solvent Naphtha (Petroleum), Heavy Aromatic (CAS Can be absorbed through the skin.

64742-94-5)

Appropriate engineering

controls

Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

Chemical respirator with organic vapor cartridge and full facepiece. Eye/face protection

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Chemical respirator with organic vapor cartridge and full facepiece. Respiratory protection

Wear appropriate thermal protective clothing, when necessary. Thermal hazards

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

## 9. Physical and chemical properties

Clear amber liquid. **Appearance** 

Physical state Liquid. **Form** Liquid. Amber Color Odor Bland

Odor threshold Not available.

5 - 7 Ha 5 % pH concentration

Melting point/freezing point Not available. Initial boiling point and boiling Decomposes

range

134.0 °F (56.7 °C) Flash point **Evaporation rate** Not available. Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits

Flammability limit - lower Not available.

(%)

Not available. Flammability limit - upper

(%)

Explosive limit - lower (%) Not available. Explosive limit - upper (%) Not available. Vapor pressure Not available. Not available. Vapor density Not available. Relative density

Solubility(ies)

Emulsifiable Solubility (water) Partition coefficient Not available.

(n-octanol/water)

Not available. **Auto-ignition temperature** Not available. **Decomposition temperature Viscosity** > 20.5 mm<sup>2</sup>/s

Material name: R-56 SDS US

1175 Version #: 02 Revision date: 09-26-2017 Issue date: 02-23-2016

104 °F (40 °C) Viscosity temperature

Other information

**Density** 8.26 lb/gal 10 - 14 % Percent volatile 77 °F (25 °C) Percent volatile

temperature

10. Stability and reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport. Reactivity

**Chemical stability** Material is stable under normal conditions. Possibility of hazardous Hazardous polymerization does not occur.

reactions

Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the Conditions to avoid

flash point. Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

No hazardous decomposition products are known.

## 11. Toxicological information

### Information on likely routes of exposure

Prolonged inhalation may be harmful. Inhalation

Causes skin irritation. Skin contact

Causes serious eye damage. Eye contact

Expected to be a low ingestion hazard. Ingestion

Symptoms related to the physical, chemical and

toxicological characteristics Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Skin irritation. May cause

redness and pain.

#### Information on toxicological effects

#### **Acute toxicity**

Addic toxidity		
Components	Species	Test Results
1,2,4-Trimethylbenzene (CA	AS 95-63-6)	
<u>Acute</u>		
Dermal		
LD50	Rat	3440 mg/kg, 24 Hours
Inhalation		
Vapor		
LC50	Mouse, Rat	2000 - 9833 mg/m3, 12 Hours
LC50	Rat	10200 mg/m3, 4 Hours
Oral		
LD50	Rat	6000 mg/kg
		3280 mg/kg
Proprietary Surfactant Blenc	d Component 3	
A4-		

**Acute** Oral Liquid

LD50

Rat 300 - 2000 mg/kg

Solvent Naphtha (Petroleum), Heavy Aromatic (CAS 64742-94-5)

**Acute Dermal** 

LD50 > 2000 mg/kg

> 2000 mg/kg, 24 Hours

Rabbit > 4000 mg/kg, 24 Hours

Material name: R-56 SDS US

Components	Species	Test Results
	Rat	> 2000 mg/kg, 24 Hours
Inhalation		
LC50	-	> 7.5 mg/l, 6 Hours
Aerosol		
LC50	Rat	> 7.5 mg/l, 6 Hours
		> 5.2 mg/l, 4 Hours
LC50	Rat	> 2.7 mg/m3, 4 Hours
Vapor		
LC50	Rat	> 0.1 mg/l, 8 Hours
Oral		
LD100	Rat	5000 mg/kg
LD50	Rat	5800 mg/kg
Solvent Naphtha (Petroleu	m), Light Aromatic (CAS 64742-95-6)	
<u>Acute</u>		
Dermal		
LD50	Rabbit	> 3750 mg/kg, 24 Hours
Inhalation		
LC50	-	> 7.5 mg/l, 6 Hours
Vapor		
LC50	Rat	> 5200 mg/m3, 4 Hours
		> 5.36 mg/l, 4 Hours
		> 5.1 mg/l, 4 Hours
Oral		
LD100	Rat	5000 mg/kg
LD50	Rat	5800 mg/kg

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

**Skin corrosion/irritation** Causes skin irritation.

Serious eye damage/eye

irritation

Causes serious eye damage.

Respiratory or skin sensitization

Respiratory sensitization Not available.

**Skin sensitization** This product is not expected to cause skin sensitization.

**Germ cell mutagenicity**No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

**Carcinogenicity** Suspected of causing cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

**US. National Toxicology Program (NTP) Report on Carcinogens** 

Not listed.

**Reproductive toxicity**This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity - single exposure

Not classified.

Specific target organ

Not classified.

toxicity - repeated

exposure

Aspiration hazard Not available.

**Chronic effects** Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

Material name: R-56 SDS US

## 12. Ecological information

**Ecotoxicity** The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

## 13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents and container in accordance with government regulations.

**Local disposal regulations** Dispose in accordance with all applicable regulations.

**Hazardous waste code**The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

product residues. This material and its container must be disposed of in a safe mariner (ser

Disposal instructions).

**Contaminated packaging** Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings, if applicable, even

after container is emptied.

## 14. Transport information

DOT

Not regulated as dangerous goods.

DOT BULK BULK

UN number NA1993

UN proper shipping name Transport hazard class(es) Combustible Liquid, N.O.S. (Aromatic Petroleum Distillate)

Class Combustible Liquid

Packing group III

Special precautions for user Not regulated when transported by road in a non-bulk package. Read safety instructions, SDS

and emergency procedures before handling.

IATA

UN number UN1993

**UN proper shipping name** Flammable liquid, n.o.s. (Aromatic Petroleum Distillate)

Transport hazard class(es)

Class 3
Subsidiary risk Packing group III
Environmental hazards No.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

**IMDG** 

UN number UN1993

UN proper shipping name Flammable Liquid, N.O.S. (Aromatic Petroleum Distillate), MARINE POLLUTANT

Transport hazard class(es)

Class 3
Subsidiary risk Label(s) 3
Packing group III
Environmental hazards

Marine pollutant Yes

EmS Not available.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and

Not established.

the IBC Code

Material name: R-56 SDS US

1175 Version #: 02 Revision date: 09-26-2017 Issue date: 02-23-2016

## **DOT Bulk packaging type**



IATA; IMDG



#### Marine pollutant



**General information** 

IMDG Regulated Marine Pollutant.

### 15. Regulatory information

**US federal regulations** 

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

#### TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

## Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - Yes Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No

### SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous No

chemical

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.	
1,2,4-TRIMETHYLBENZENE	95-63-6	1 - < 3	_

Material name: R-56 SDS US

#### Other federal regulations

#### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

#### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

#### **US** state regulations

## US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd.

1,2,4-Trimethylbenzene (CAS 95-63-6)

Solvent Naphtha (Petroleum), Light Aromatic (CAS 64742-95-6)

#### **US. California Proposition 65**

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

#### US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Oxirane (CAS 75-21-8) Listed: July 1, 1987 Propylene Oxide (CAS 75-56-9) Listed: October 1, 1988

US - California Proposition 65 - CRT: Listed date/Developmental toxin

Oxirane (CAS 75-21-8) Listed: August 7, 2009 US - California Proposition 65 - CRT: Listed date/Female reproductive toxin

Listed: February 27, 1987 Oxirane (CAS 75-21-8)

US - California Proposition 65 - CRT: Listed date/Male reproductive toxin Listed: August 7, 2009

Oxirane (CAS 75-21-8)

#### International Inventories

Country(s) or region Inventory name On inventory (yes/no)\*

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory Yes

## 16. Other information, including date of preparation or last revision

02-23-2016 Issue date 09-26-2017 **Revision date** 

Version # 02

NFPA ratings Health: 3

Flammability: 3 Instability: 0

NFPA ratings



#### Disclaimer

This information was developed from information on the constituent materials. No warranty is expressed or implied regarding the completeness or continuing accuracy of the information contained herein, and Wilbur-Ellis disclaims all liability for reliance thereon. The user should satisfy himself that he has all current data relevant to his particular use.

Material name: R-56 SDS US

<sup>\*</sup>A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).