

Andersons Golf Products

Turf Fertilizer

21-3-16

- Contains MUtech® nitrogen
- Provides Iron and micronutrients
- Contains Potassium Sulfate
- SGN 100 for use on greens and tees
- Low residue formulation

Guaranteed Analysis

| | |
|--|--------|
| Total Nitrogen (N) | 21.00% |
| 0.63% Ammoniacal Nitrogen | |
| 3.05% Urea Nitrogen | |
| 7.13% Water Insoluble Nitrogen | |
| 10.19% Other Water Soluble Nitrogen* | |
| Available Phosphate (P ₂ O ₅) | 3.00% |
| Soluble Potash (K ₂ O) | 16.00% |
| Sulfur (S) | 5.40% |
| 5.40% Combined Sulfur (S) | |
| Copper (Cu) | 0.10% |
| 0.02% Water Soluble Copper (Cu) | |
| Iron (Fe) | 1.00% |
| 0.03% Water Soluble Iron (Fe) | |
| Manganese (Mn) | 0.10% |
| 0.03% Water Soluble Manganese (Mn) | |
| Zinc (Zn) | 0.10% |
| 0.03% Water Soluble Zinc (Zn) | |

Plant nutrients derived from ammonium phosphate, potassium sulfate, methylene ureas, ferric oxide, ferrous sulfate, cupric oxide, cupric sulfate, manganous oxide, manganese sulfate, zinc oxide and zinc sulfate.

*10.19% Slowly available nitrogen from methylene ureas.

F002091

Information regarding the contents and levels of metals in this product is available on the internet at <http://www.regulatory-info-ap.com>.

DIRECTIONS FOR USE

Apply only as directed. Use Andersons Golf Products Turf Fertilizer 21-3-16 on actively growing greens, tees, fairways and roughs whenever a high nitrogen feeding with quick initial green-up and controlled-release nitrogen is desired.

Application Rates:

| | |
|--------------|------------------------|
| LOW RATE: | 2.25 lbs/1,000 sq. ft. |
| MEDIUM RATE: | 3.50 lbs/1,000 sq. ft. |
| HIGH RATE: | 4.80 lbs/1,000 sq. ft. |

FLORIDA APPLICATIONS:

We recommend that you follow the Florida Green Industries BMP's at http://www.flaes.org/pdf/BMP_Book_final.pdf

We recommend that you follow the Florida Golf Course BMP's at <http://www.flaes.org/pdf/gfbmp07.pdf>

For all applications:

- For use on greens, tees, fairways and roughs.
- Apply to dry foliage.
- Water in after application with a minimum of 0.2 inches to help move particles into the turf canopy.
- Do not collect clippings for at least one mowing following application to avoid particle pick-up.

Cool Season Grasses:

- Apply at LOW or MEDIUM RATE.
- Apply at HIGH RATE in spring or fall when deeper greening is desired or to correct or prevent iron deficiencies.
- Exception: Apply at LOW RATE in mid-summer when temperatures are above 80°F.

Warm Season Grasses:

- Apply at the LOW or MEDIUM RATE.
- HIGH RATE may be used to help bring grass out of dormancy in early spring (such as bermudagrass) or to correct or prevent iron deficiencies.
- Exception: Apply at LOW RATE during mid-summer when temperatures are extreme (90°F or above).

Note: This product contains the micronutrient iron for extra greening and to help prevent iron deficiency. Iron may stain concrete and other surfaces. Misapplied product to these surfaces should be removed promptly by sweeping or blowing. Do not wash off with water.

Do not apply near water, storm drains or drainage ditches. Do not apply if heavy rain is expected. Apply this product only to your lawn and sweep any product that lands on the driveway, sidewalk or street, back onto your lawn.

STORAGE AND USE

Store in a clean, dry place.
Reseal opened bag by folding top down and securing.
Use only in clean, dry spreaders.
Do not leave unused product in spreaders.

IMPORTANT: READ BEFORE USE:

Read the entire Directions for Use and the Warranty Disclaimer and Limitation of Liability before using this product. If terms are not acceptable, return the unopened product container at once. By using this product, user or Buyer accepts the following Warranty Disclaimer and Limitation of Liability:

WARRANTY DISCLAIMER and LIMITATION of LIABILITY:

Manufacturer warrants that this product conforms to the chemical description on the label and is reasonably fit for the purposes stated on the label when used in strict accordance with the directions. Manufacturer makes NO OTHER EXPRESS OR IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. To the extent consistent with applicable law, it is Manufacturer's intent to LIMIT ANY LIABILITY FOR SPECIAL, CONSEQUENTIAL OR INCIDENTAL ECONOMIC DAMAGES to refund of purchase price or replacement of product, at Buyer's choice. To the extent consistent with applicable law, Manufacturer DISCLAIMS ANY LIABILITY FOR COMPENSATORY OR OTHER DAMAGES ARISING OUT OF ANY USE CONTRARY TO LABEL DIRECTIONS.

LEGAL RIGHTS:

THIS LIMITED WARRANTY GIVES YOU SPECIFIC LEGAL RIGHTS; YOU MAY HAVE OTHER RIGHTS THAT VARY FROM STATE/JURISDICTION TO STATE/JURISDICTION. Product of U.S.A.

Manufactured by:
The Andersons, Inc.
P.O. Box 119
Maumee, OH 43537
www.andersonsplantnutrient.com

Tee Time and MUtech are registered trademarks of The Andersons, Inc.



| SUGGESTED SPREADER SETTINGS | | | | | |
|--|--------------|-------------------|------------------------------------|---------------------------------------|-------------------------------------|
| These suggested spreader settings are not intended to replace calibration. Please calibrate your spreader prior to applying product. | | | | | |
| 50 lbs. feeds 22,200 sq. ft. (0.51 acre) with 0.47 lbs. N/1,000 sq. ft. at the LOW RATE | | | | | |
| 50 lbs. feeds 14,200 sq. ft. (0.33 acre) with 0.73 lbs. N/1,000 sq. ft. at the MEDIUM RATE | | | | | |
| 50 lbs. feeds 10,400 sq. ft. (0.24 acre) with 1.00 lbs. N/1,000 sq. ft. at the HIGH RATE | | | | | |
| SPREADER | GROUND SPEED | WIDTH OF COVERAGE | SPREADER SETTINGS | | |
| | | | LOW RATE 2.25 lbs/1,000 sq. ft. | MEDIUM RATE 3.50 lbs/1,000 sq. ft. | HIGH RATE 4.80 lbs/1,000 sq. ft. |
| Andersons Model 2000 / AccuPro 2000 (cone 9); Andersons 2000 SR / SR-2000 (cone 9) | 3 mph | 10 feet | I 1/2 | J 1/2 | K 3/4 |
| Andersons SSD / SS-2 Drop | 3 mph | overlap wheels | 3 1/4 | 4 | 4 1/2 |
| Scotts R-8, R-8A (cone 9) | 3 mph | 10 feet | H 1/4 | I | J |
| Lesco 020093 (pattern 0.25) | 3 mph | 8 feet | C 1/2 | D | D 1/2 |
| Lesco 705698 (pattern 0.25) | 3 mph | 8 feet | 9 | 10 | 11 |

SGN 100
Net Wt. 50 Lbs. (22.68 kg)



AGC217M50.40