

TOPCOAT™

ORGANIC STRESS PROTECTOR



TOPCOAT is a blend of organic oil and inert ingredients specifically formulated for foliar application. It is designed to help protect leaves and fruit from adverse weather conditions such as heat and cold stress.

DIRECTIONS AND USE

Water plants thoroughly and allow time to take up water before applying **TOPCOAT**. Thoroughly coat upper and lower surface of all leaves and stems to run off. Apply 24-48 hours in advance of transplanting. If applied to edible foodstuff, last application should provide time for product to biodegrade prior to last harvest (30-45 days). Thoroughly wash sprayed fruit. Flush spray equipment with clean water immediately after use. For removal of dried product, soak in water until softened.

Ornamentals:

Outside: Spray 3 gal. of **TOPCOAT** per 100 gal. of water (2 tbsp. per 1 quart of water) to run off.

Indoor: Spray 4 tsp. of **TOPCOAT** per 1 quart of water to run off. Low light: 3 tsp. of **TOPCOAT** per 1 quart of water.

Blooming Plants:

Spraying 7 qts. of **TOPCOAT** per 100 gal. of water (4 tsp. per 1 quart of water) may extend bloom by reducing moisture loss.

Propagation: 6 gal. of **TOPCOAT** per 100 gal. of water (4 tsp. per 1 quart of water).

Vegetables:

Spray 3 gal. of **TOPCOAT** per 100 gal. of water (2 tbsp. per 1 quart of water) 24-48 hours before transplanting.

ACTIVE INGREDIENTS:

80% Cold Pressed Linseed Oil

Inert Ingredients:

Sorbitol, Oleic Acid, Lauric Acid and Steric Acid.

REDUCES MOISTURE LOSS

Ornamentals - Gardens - Lawns

- Frost
- Heat
- Freeze
- Sudden Climate Change
- Drought
- Winds
- Transplant Shock

KEEP OUT OF REACH OF CHILDREN

MANUFACTURED BY:

JH Biotech, Inc.

P.O. Box 3538

Ventura, California 93006

Net Contents:

- ☐ 1 Pint (0.47 liter)
- ☐ 2.5 Gallons (9.45 liters)
- ☐ 2 x 2.5 Gallons (18.9 liters)
- ☐ 5 Gallons (18.9 liters)
- ☐ 55 Gallons (207.9 liters)

Weight per Gallon: 10.5 lbs. (4.8 kg)

Spray 2 qts. of **TOPCOAT** per 100 gal. of water or 4 tsp. per 1 quart of water after pollination as needed.

Fruiting Trees:

Spray 3 gal. of **TOPCOAT** per 100 gal. of water (2 tbsp. per 1 quart of water) in early spring before danger of frost.

Spray 2 qts. of **TOPCOAT** per 100 gal. of water or 4 tsp. per 1 quart of water after fruit set every 30 days.

Lawns:

Spray 2 qts. of **TOPCOAT** per 100 gal. of water or 4 tsp. per 1 quart of water after every third cutting.

Spray 3 gal. of **TOPCOAT** per 100 gal. of water (2 tbsp. per 1 quart of water) to stressed areas after watering thoroughly.

Frost and Freeze Protection:

Spray 3 gal. of **TOPCOAT** per 100 gal. of water (2 tbsp. per 1 quart of water) to thoroughly coat entire plant including upper and lower surface of leaves before danger of frost occurs.

CAUTION: Neutralize all spray equipment that has been used to spray herbicides, high acid fertilizers, or calcium and magnesium. DO NOT FREEZE

LIMITED WARRANTY

Manufacturer or seller makes no warranty, whether expressed or implied, concerning the use of this product other than for the purposes indicated on the label. Neither manufacturer nor seller shall be liable for any injury or damage caused by this product due to misuse, mishandling, or any application not specifically described on the label.

Lot #:

JH Biotech, Inc.®

0243-D-A-1