

ContecDG[®]

Dispersing Granule Technology

0-0-12



FEATURES & USE TIPS:

- Higher visibility formulation
- Patented dispersing granule formula
- Greatly reduces fertilizer loss due to ball, shoe & mower pickup.
- Contains magnesium to correct deficiencies.
- K-Mag to help root systems develop and build turf resistance to stress.

PRODUCT SPECIFICATIONS:

K - as K₂O - (12%):	Sulfate of Potash Magnesia
S - (12.00%):	Combined Sulfur
Mg - (24.00%):	Magnesium

PRODUCT CODE:

AGCK12MDG4

Date: 030410
Supersedes: 000000
Label: B10

PRODUCT CHARACTERISTICS:

Product Type:

Dispersible granular nutrient

Particle Size:

SGN: 75

Net Weight:

40 lbs.

Coverage:

9,500 sq. ft.
@ Medium Rate

Andersons Golf Products and ContecDG[®] are registered trademarks of The Andersons, Inc.

To order, contact your local Andersons Golf Products distributor.

For more information, contact Andersons at our website: www.andersonsgolfproducts.com or call 1-800-225-2639.

Following is a specimen label that may at some point be revised or otherwise become out of date. It is intended as a guide in providing general information regarding the use of this product. Always read and follow the label on the product container.

PRODUCT SHEET



0-0-12

- Specially designed for use on greens & tees
- Contains magnesium

GUARANTEED ANALYSIS

Soluble Potash (K ₂ O)	12.00%
Magnesium (Mg)	24.00%
6.00% Water Soluble Magnesium (Mg)	
Sulfur (S)	12.00%
12.00% Combined Sulfur (S)	
Plant nutrients derived from sulfate of potash magnesia and magnesium oxide.	
Chlorine (Cl) Max	0.84%

U.S. Patent #6,884,756

Information regarding the contents and levels of metals in this product is available on the internet at <http://www.regulatory-info-ap.com>

DIRECTIONS FOR USE

Apply only as directed during the growing season.
 Use Andersons Golf Products ContecDG® Dispersing Granule Technology 0-0-12 for greens, tees and other fine turf areas where a potassium fertilization is desired or when magnesium is needed to help correct or prevent deficiencies during the growing season.

Watering in this product will disperse each granule into thousands of particles. This will facilitate the movement of the nutrients into the soil. This particle dispersion will also greatly reduce ball, shoe and mower pickup - minimizing nutrient loss.

Application to wet, close-cut golf turf may result in foliar staining, which will discolor the turf to a brown/black appearance. This will occur even if immediate irrigation or rainfall occurs. Be sure to apply this product to dry turf only.

Application Rates:

LIGHT:	2.08 lbs/1,000 sq. ft.
LOW:	3.13 lbs/1,000 sq. ft.
MEDIUM:	4.17 lbs/1,000 sq. ft.

FLORIDA APPLICATIONS: We recommend that you follow the Florida Green Industries BMP's at http://www.flaes.org/pdf/BMP_Book_final.pdf

FLORIDA APPLICATIONS: We recommend that you follow the Florida Golf Course BMP's at <http://www.flaes.org/pdf/gfifbmp07.pdf>

For all applications:
 Immediately after application, for optimum results, apply a minimum of 0.1 to 0.2 inches of water to disperse the granules.

Recent research has shown that well-maintained turf is an effective environmental buffer that prevents pollutants from entering our natural water-bodies. To help protect these natural resources, avoid applying product to sidewalks, driveways, roadways, and other impervious surfaces. Sweep any misplaced granules back onto the area you are treating immediately after application, since storm drains often empty directly to nearby waterways.

Storage and Use:

- Store in a clean, dry place.
- Reseal opened bag by folding top down and securing.
- Use only clean, dry spreaders.
- Do not leave unused product in spreaders.

IMPORTANT: READ BEFORE USE:

Read the entire Directions for Use and the Warranty Disclaimer and Limitation of Liability before using this product. If terms are not acceptable, return the unopened product container at once. By using this product, user or Buyer accepts the following Warranty Disclaimer and Limitation of Liability:

WARRANTY DISCLAIMER and LIMITATION of LIABILITY:

Manufacturer warrants that this product conforms to the chemical description on the label and is reasonably fit for the purposes stated on the label when used in strict accordance with the directions. Manufacturer makes NO OTHER

EXPRESS OR IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. To the extent consistent with applicable law, it is Manufacturer's intent to LIMIT ANY LIABILITY FOR SPECIAL, CONSEQUENTIAL OR INCIDENTAL ECONOMIC DAMAGES to refund of purchase price or replacement of product, at Buyer's choice. To the extent consistent with applicable law, Manufacturer DISCLAIMS ANY LIABILITY FOR COMPENSATORY OR OTHER DAMAGES ARISING OUT OF ANY USE CONTRARY TO LABEL DIRECTIONS. Use contrary to label directions is not permitted.

LEGAL RIGHTS:

THIS LIMITED WARRANTY GIVES YOU SPECIFIC LEGAL RIGHTS; YOU MAY HAVE OTHER RIGHTS THAT VARY FROM STATE/JURISDICTION TO STATE/JURISDICTION.

Product of USA

Manufactured by:
 The Andersons Lawn Fertilizer Division, Inc.
 P. O. Box 119
 Maumee, Ohio 43537
www.andersonsgolfproducts.com

Andersons Golf Products and ContecDG are registered trademarks of The Andersons, Inc.

Suggested Spreader Settings

These suggested spreader settings are not intended to replace calibration. Please calibrate your spreader before applying product.

40 lbs. feeds 19,200 sq. ft. (0.44 acre) with 0.25 lb. K₂O/1,000 sq. ft. at the LIGHT RATE (2.08 lbs/1,000 sq. ft.)
40 lbs. feeds 12,700 sq. ft. (0.29 acre) with 0.38 lb. K₂O/1,000 sq. ft. at the LOW RATE (3.13 lbs/1,000 sq. ft.)
40 lbs. feeds 9,500 sq. ft. (0.22 acre) with 0.50 lb. K₂O/1,000 sq. ft. at the MEDIUM RATE (4.17 lbs/1,000 sq. ft.)

SPREADER	GROUND SPEED	WIDTH OF COVERAGE	SPREADER SETTINGS		
			LIGHT RATE 2.08 lbs/1,000 sq. ft.	LOW RATE 3.13 lbs/1,000 sq. ft.	MEDIUM RATE 4.17 lbs/1,000 sq. ft.
Andersons AccuPro 2000, SF-2000 (cone 9)	3 mph	10 feet	I	J	K 1/2
Andersons SS-2 Drop	3 mph	overlap wheels	3	3 3/4	4 1/2
Scotts R-8, R-8A (cone 9)	3 mph	10 feet	H	I	J
Lely Models WTR, WFR, HR, 1250 (PTO at 450 rpm) (Pattern II-B)	4.5 mph	26 feet	3 3/4	4 1/4	5
Vicon (03 Series)	4.5 mph	22 feet	13	16	18

SGN 75

Net Wt. 40 Lbs (18.14 kg)



AGCK12MDG4

B10 (AGCBLKPCDGB)