

The Andersons® Professional Turf™ Products
21-0-21

- Contains NS-54™ proprietary coated slow release nitrogen to provide uniform growth with extended feeding.
- Contains Iron for improved turf color
- SGN 215 for use on fairways, roughs and other turf areas.

GUARANTEED ANALYSIS

Total Nitrogen (N).....	21.00%
21.00% Urea Nitrogen*	
Soluble Potash (K ₂ O).....	21.00%
Iron (Fe).....	2.00%
Sulfur (S).....	6.81%

 1.46% Free Sulfur
 5.35% Combined Sulfur

Plant nutrients derived from urea, potassium chloride, potassium sulfate, polymer coated sulfur coated urea and ferric oxide.

Chlorine (Cl) Max..... 4.45%
*15.75% Slowly available nitrogen from polymer coated sulfur coated urea.

F292

Information regarding the contents and levels of metals in this product is available on the internet at <http://www.regulatory-info-ap.com>

DIRECTIONS FOR USE

Apply only as directed. Apply during the growing season.

Application Rates:

LOW: 2.38 lbs/1,000 sq. ft.
MEDIUM: 3.57 lbs/1,000 sq. ft.
HIGH: 4.76 lbs/1,000 sq. ft.

For all applications:

- Apply to dry foliage.
- Water in after application with a minimum of 0.2 inches to help move particles into the turf canopy.
- Do not collect clippings for at least one mowing following application to avoid particle pick-up.

Cool Season Grasses:

- Apply at the MEDIUM RATE.
- Apply at the LOW RATE when temperatures exceed 85°F.

Warm Season Grasses:

- Apply at the MEDIUM RATE every 4-6 weeks during the period of active growth.

STORAGE AND USE

Store in a clean, dry place.
Reseal opened bag by folding top down and securing.
Use only in clean, dry spreaders.
Do not leave unused product in spreaders.

Recent research has shown that well-maintained turf is an effective environmental buffer that prevents pollutants from entering our natural water bodies. To help protect these natural resources, avoid applying product to sidewalks, driveways, roadways, and other impervious surfaces. Sweep any misplaced granules back onto the area you are treating immediately after application, since storm drains often empty directly to nearby waterways.

This product contains the micronutrient iron for extra greening and to help prevent iron deficiency. Iron may stain concrete and other surfaces. Misapplied product to these surfaces should be removed promptly by sweeping or blowing. DO NOT WASH OFF WITH WATER.

IMPORTANT: READ BEFORE USE:

Read the entire Directions for Use and the Warranty Disclaimer and Limitation of Liability before using this product. If terms are not acceptable, return the unopened product container at once. By using this product, user or Buyer accepts the following Warranty Disclaimer and Limitation of Liability:

WARRANTY DISCLAIMER and LIMITATION of LIABILITY:

Manufacturer warrants that this product conforms to the chemical description on the label and is reasonably fit for the purposes stated on the label when used in strict accordance with the directions. Manufacturer makes NO OTHER EXPRESS OR IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. To the extent consistent with applicable law, it is Manufacturer's intent to LIMIT ANY LIABILITY FOR SPECIAL, CONSEQUENTIAL OR INCIDENTAL ECONOMIC DAMAGES to refund of purchase price or replacement of product, at Buyer's choice. To the extent consistent with applicable law, Manufacturer DISCLAIMS ANY LIABILITY FOR COMPENSATORY OR OTHER DAMAGES ARISING OUT OF ANY USE CONTRARY TO LABEL DIRECTIONS. Use contrary to label directions is not permitted.

LEGAL RIGHTS:

THIS LIMITED WARRANTY GIVES YOU SPECIFIC LEGAL RIGHTS; YOU MAY HAVE OTHER RIGHTS THAT VARY FROM STATE/JURISDICTION TO STATE/JURISDICTION.

Product of U.S.A.

Manufactured by:
The Andersons Lawn Fertilizer Division, Inc.
P.O. Box 119
Maumee, OH 43537
www.andersonslawnproducts.com

The Andersons logo is a registered trademark of The Andersons, Inc.; Professional Turf and NS-54 are trademarks of The Andersons, Inc.

Suggested Spreader Settings					
These suggested spreader settings are not intended to replace calibration. Please calibrate your spreader before applying product.					
50 lbs. covers 21,000 sq. ft. (0.48 acre) with 0.50 lbs. N/1,000 sq. ft. at the LOW RATE					
50 lbs. covers 14,000 sq. ft. (0.32 acre) with 0.75 lbs. N/1,000 sq. ft. at the MEDIUM RATE					
50 lbs. covers 10,500 sq. ft. (0.24 acre) with 1.00 lbs. N/1,000 sq. ft. at the HIGH RATE					
SPREADER	GROUND SPEED	WIDTH OF COVERAGE	SPREADER SETTINGS		
			LOW RATE 2.38 lbs/1,000 sq.ft.	MEDIUM RATE 3.57 lbs/1,000 sq.ft.	HIGH RATE 4.76 lbs./1,000 sq.ft.
Andersons AccuPro 2000, SR-2000 (cone 4)	3 mph	12 feet	K 1/4	L 1/2	M 3/4
Scotts R-8, R-8A (cone 4)	3 mph	12 feet	J 1/4	K 1/2	L 3/4
Lesco 020093 (pattern 0.5)	3 mph	10 feet	D 3/4	E 1/2	G 1/4
Lesco 705698 (pattern 0.5)	3 mph	10 feet	11 1/2	13	16 1/2
Lely Models WTR, WFR, HR, 1250 (PTO at 450 rpm) Pattern I	4.5 mph	40 feet	4 3/4	5 1/2	6 1/4
Vicon 03 Series	4.5 mph	36 feet	20	25	30

SGN 215
Net Wt. 50 Lbs. (22.68 kg)



APT21155

K9 (APTBLKPGRNB)