



Bonide Pruning Sealer

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name : Bonide Pruning Sealer
Product code : 225

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Bonide Products, Inc.
6301 Sutliff Road
Oriskany, NY 13424
T (315) 736-8231
www.bonide.com

1.4. Emergency telephone number

Emergency number : CHEMTREC - 1 (800) 424-9300 and/or 1 (703) 527-3887

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture


Classification (GHS-US)

Flam. Liq. 2 H225
STOT SE 1 H370
STOT RE 1 H372

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

H225 - Highly flammable liquid and vapor
H370 - Causes damage to organs.
H372 - Causes damage to organs through prolonged or repeated exposure.

Precautionary statements (GHS-US) :

P210 - Keep away from sparks/ignition sources. - No smoking
P233 - Keep container tightly closed
P240 - Ground/bond container and receiving equipment
P242 - Use only non-sparking tools
P243 - Take precautionary measures against static discharge
P260 - Do not breathe vapours
P264 - Wash hands thoroughly after handling
P270 - Do not eat, drink or smoke when using this product
P280 - Wear gloves/eye protection
P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
P314 - Get medical advice and attention if you feel unwell
P321 - Specific treatment (see first aid section on this label)
P370+P378 - In case of fire: Use Dry chemical, CO2, water spray or regular foam for extinction
P403+P235 - Store in a well-ventilated place. Keep cool
P405 - Store locked up
P501 - Dispose of contents/container to in accordance with local/national regulations

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS-US)

No data available

Bonide Pruning Sealer

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 3: Composition/information on ingredients

Mixture

Name	Product identifier	%	Classification (GHS-US)
solvent naphtha(petroleum), medium aliph.	(CAS No) 64742-88-7	15 - 20	STOT RE 1, H372 Asp. Tox. 1, H304
Hydrous Amuminum Silicate	(CAS No) 1335-30-4	8 - 12	Not classified
methanol	(CAS No) 67-56-1	2 - 4	Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation:dust,mist), H331 STOT SE 1, H370

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice. Call a POISON CENTER or doctor/physician.
First-aid measures after inhalation	: Remove to fresh air and keep at rest in a position comfortable for breathing.
First-aid measures after skin contact	: Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing.
First-aid measures after eye contact	: Remove contact lenses, if present and easy to do. Continue rinsing. Rinse cautiously with water for several minutes. Obtain medical attention if pain, blinking or redness persist.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries	: Causes damage to organs through prolonged or repeated exposure.
-------------------	---

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

suitable extinguishing media	: Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Highly flammable liquid and vapor.
Explosion hazard	: May form flammable/explosive vapor-air mixture.

5.3. Advice for firefighters

Firefighting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Avoid (reject) fire-fighting water to enter environment.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Remove ignition sources. Use special care to avoid static electric charges.
------------------	---

6.1.1. For non-emergency personnel

Emergency procedures	: Evacuate unnecessary personnel.
----------------------	-----------------------------------

6.1.2. For emergency responders

Protective equipment	: Equip cleanup crew with proper protection. Avoid breathing vapours.
Emergency procedures	: Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up	: Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.
-------------------------	--

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

Bonide Pruning Sealer

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Additional hazards when processed : Handle empty containers with care because residual vapors are flammable.
- Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eat, drink or smoke and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Use only non-sparking tools. Do not breathe vapours.
- Hygiene measures : Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment.
- Storage conditions : Store in original container. Keep in fireproof place. Keep container tightly closed.
- Incompatible products : Strong bases. strong acids.
- Incompatible materials : Sources of ignition. Heat sources.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

methanol (67-56-1)		
USA ACGIH	ACGIH TWA (ppm)	200 ppm
USA ACGIH	ACGIH STEL (ppm)	200 ppm

8.2. Exposure controls

- Personal protective equipment : Avoid all unnecessary exposure.
- Hand protection : Wear protective gloves.
- Eye protection : Chemical goggles or safety glasses.
- Respiratory protection : Where exposure through inhalation may occur from use, respiratory protection equipment is recommended.
- Other information : When using, do not eat, drink or smoke.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

- Physical state : Liquid
- Appearance : Black Viscous liquid.
- Color : Black.
- Odor : Petroleum Solvent.
- Odor threshold : No data available
- pH : No data available
- Relative evaporation rate (butyl acetate=1) : No data available
- Melting point : No data available
- Freezing point : No data available
- Boiling point : No data available
- Flash point : > 105 °F
- Self ignition temperature : No data available
- Decomposition temperature : No data available
- Flammability (solid, gas) : No data available
- Vapor pressure : No data available
- Relative vapor density at 20 °C : No data available
- Relative density : 1.11
- Solubility : Negligible.
- Log Pow : No data available
- Log Kow : No data available
- Viscosity, kinematic : No data available
- Viscosity, dynamic : No data available

Bonide Pruning Sealer

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Explosive properties	: No data available
Oxidizing properties	: No data available
Explosive limits	: No data available

9.2. Other information

VOC content	: 14 %
-------------	--------

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Extremely high or low temperatures. Open flame.

10.5. Incompatible materials

strong acids. Strong bases.

10.6. Hazardous decomposition products

Carbon monoxide. Carbon dioxide. May release flammable gases.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

solvent naphtha(petroleum), medium aliph. (64742-88-7)

LD50 oral rat	> 5000 mg/kg body weight (Rat; Equivalent or similar to OECD 420; Experimental value)
LD50 dermal rabbit	> 2000 mg/kg body weight (Rabbit; Experimental value; Equivalent or similar to OECD 402)

methanol (67-56-1)

LD50 oral rat	> 5000 mg/kg (Rat; BASF test; Literature study; 1187-2769 mg/kg bodyweight; Rat; Weight of evidence)
LD50 dermal rabbit	15800 mg/kg (Rabbit; Literature study)
LC50 inhalation rat (mg/l)	85 mg/l/4h (Rat; Literature study)
LC50 inhalation rat (ppm)	64000 ppm/4h (Rat; Literature study)

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Causes damage to organs.

Specific target organ toxicity (repeated exposure) : Causes damage to organs through prolonged or repeated exposure.
Causes damage to organs through prolonged or repeated exposure

Aspiration hazard	: Not classified
Potential Adverse human health effects and symptoms	: Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1. Toxicity

solvent naphtha(petroleum), medium aliph. (64742-88-7)

Threshold limit algae 1	1 - 3,72 h; Pseudokirchneriella subcapitata; Cell numbers
-------------------------	---

Bonide Pruning Sealer

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

methanol (67-56-1)	
LC50 fish 1	15400 mg/l (96 h; Lepomis macrochirus; Lethal)
EC50 Daphnia 1	> 10000 mg/l (48 h; Daphnia magna; Lethal)
LC50 fish 2	10800 mg/l 96 h; Salmo gairdneri (Oncorhynchus mykiss)
EC50 Daphnia 2	24500 mg/l (48 h; Daphnia magna; Locomotor effect)
Threshold limit other aquatic organisms 1	6600 mg/l (16 h; Pseudomonas putida)
Threshold limit algae 1	530 mg/l (192 h; Microcystis aeruginosa)
Threshold limit algae 2	8000 mg/l (168 h; Scenedesmus quadricauda)

12.2. Persistence and degradability

Bonide Pruning Sealer	
Persistence and degradability	Not established.

solvent naphtha(petroleum), medium aliph. (64742-88-7)	
Persistence and degradability	Readily biodegradable in water. Adsorbs into the soil.

Hydrous Amuminum Silicate (1335-30-4)	
Persistence and degradability	Biodegradability in soil: not applicable. No (test)data on mobility of the components available.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable

methanol (67-56-1)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Highly mobile in soil.
Biochemical oxygen demand (BOD)	0.6 - 1.12 g O ₂ /g substance
Chemical oxygen demand (COD)	1.42 g O ₂ /g substance
ThOD	1.5 g O ₂ /g substance
BOD (% of ThOD)	0.8 % ThOD

12.3. Bioaccumulative potential

Bonide Pruning Sealer	
Bioaccumulative potential	Not established.

solvent naphtha(petroleum), medium aliph. (64742-88-7)	
Bioaccumulative potential	No bioaccumulation data available.

Hydrous Amuminum Silicate (1335-30-4)	
Bioaccumulative potential	No bioaccumulation data available.

methanol (67-56-1)	
BCF fish 1	< 10 (72 h; Leuciscus idus)
BCF fish 2	1 (72 h; Cyprinus carpio; Blood)
Log Pow	-0.77 (Experimental value; Other)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

12.4. Mobility in soil

methanol (67-56-1)	
Surface tension	0.023 N/m (20 °C)

12.5. Other adverse effects

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.
Additional information : Handle empty containers with care because residual vapors are flammable.
Ecology - waste materials : Avoid release to the environment.

Bonide Pruning Sealer

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 14: Transport information

In accordance with DOT

No dangerous good in sense of transport regulations

Additional information

Other information : No supplementary information available.

ADR

Transport document description :

Transport by sea

No additional information available

Air transport

No additional information available

SECTION 15: Regulatory information

:

15.1. US Federal regulations

Bonide Pruning Sealer

Not listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

No additional information available

EU-Regulations

No additional information available

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Classification according to Directive 67/548/EEC or 1999/45/EC

Not classified

15.2.2. National regulations

No additional information available

15.3. US State regulations

No additional information available

SECTION 16: Other information

Other information : None.

Full text of H-phrases: see section 16:

Acute Tox. 3 (Dermal)	Acute toxicity (dermal) Category 3
Acute Tox. 3 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral) Category 3
Asp. Tox. 1	Aspiration hazard Category 1
Flam. Liq. 2	Flammable liquids Category 2
STOT RE 1	Specific target organ toxicity (repeated exposure) Category 1
STOT SE 1	Specific target organ toxicity (single exposure) Category 1
H225	Highly flammable liquid and vapor
H301	Toxic if swallowed
H304	May be fatal if swallowed and enters airways
H311	Toxic in contact with skin
H331	Toxic if inhaled
H370	Causes damage to organs
H372	Causes damage to organs through prolonged or repeated exposure

Bonide Pruning Sealer

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SDS US (GHS HazCom 2012) - Pesticides

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.