



**THE ANDERSONS
MATERIAL SAFETY DATA SHEET**

PRODUCT CODE: AGC251M50

DATE PREPARED: 04/05/90

SECTION I: PRODUCT IDENTITY

PRODUCT NAME: The Andersons Golf Turf Fertilizer 25-5-12

MFR INFO: The Andersons Lawn Products
P.O. Box 119
Maumee, Ohio 43537

FOR EMERGENCY: (800) 757-8951
FOR INFORMATION: (419) 891-2957

CURRENT AS OF: 5/6/02

SECTION II: HAZARDOUS INGREDIENTS / IDENTITY INFORMATION

HAZARDOUS COMPONENT	OSHA PEL	ACGIH TLV
Diammonium phosphate (CAS # 7783-28-0)	15 mg/m ³ (total) 5 mg/m ³ (respirable)	10 mg/m ³
Potash (CAS # 7447-40-7)	15 mg/m ³ (total) 5 mg/m ³ (respirable)	10 mg/m ³
Urea (CAS # 57-13-6)	15 mg/m ³ (total) 5 mg/m ³ (respirable)	10 mg/m ³
Limestone (CAS # 1317-65-3)	15 mg/m ³ (total) 5 mg/m ³ (respirable)	10 mg/m ³
Sulfur coated urea (CAS # Not listed)		
Inorganic iron mix (CAS # Not listed)	15 mg/m ³ (total) 5 mg/m ³ (respirable)	10 mg/m ³
Micronutrient mix (CAS # Not listed)	15 mg/m ³ (total) 5 mg/m ³ (respirable)	10 mg/m ³

SECTION III: PHYSICAL DATA

BOILING POINT: NA EVAPORATION RATE: NA pH: NA
VAPOR DENSITY: NA VAPOR PRESSURE: NA
MELTING POINT: NA SPECIFIC GRAVITY: NA
SOLUBILITY (IN WATER): Partially soluble
APPEARANCE AND ODOR: Multi-colored granular mix, with slight ammonia / sulfur odor

SECTION IV: FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: Not flammable FLAMMABLE LIMITS: NA
EXTINGUISHING MEDIA: Use media suitable for surrounding fire
SPECIAL FIRE FIGHTING PROCEDURES:
Wear full protective clothing and positive-pressure self-contained breathing apparatus
UNUSUAL FIRE AND EXPLOSION HAZARDS:
Decomposition products may be toxic; sulfur will burn when separated from molten urea

SECTION V: REACTIVITY DATA

CONDITIONS TO AVOID: Excessive heat (greater than 200°F)
INCOMPATIBILITY: Strong oxidizers, caustics, acids, hypochlorites
HAZARDOUS DECOMPOSITION PRODUCTS: HCN, NO_x, CO_x, NH₃, PO_x, cyanuric acid
Product is stable and hazardous polymerization will not occur. May release ammonia on standing.

SECTION VI: PERSONAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: NIOSH approved particulate respirator, if required
EYE PROTECTION: Safety glasses with sideshields, goggles, or faceshield are recommended
SKIN PROTECTION: Long sleeves, rubber gloves recommended
VENTILATION: Local exhaust ventilation recommended

SECTION VII: HEALTH HAZARD DATA

HEALTH HAZARDS: Dust may be irritating to the nose, throat, and respiratory tract, and may cause sore throat, coughing, and shortness of breath. Skin irritation may result; repeated or prolonged skin exposures may result in dermatitis. Dust may also be irritating to the eyes, causing redness and watering. Prolonged eye exposure may cause conjunctivitis and corneal damage. Ingestion may result in sore throat, abdominal pain, nausea, and diarrhea. Ingestion of large amounts of sulfur may lead to hydrogen sulfide poisoning due to bacterial conversion of sulfur in the colon.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: Pre-existing eye, skin or respiratory conditions

FIRST AID PROCEDURES:

IF SWALLOWED: If victim is alert and not convulsing, give one glass of water to dilute material, but DO NOT induce vomiting. Seek immediate medical attention.

IF INHALED: Move victim to fresh air. Seek medical attention if irritation persists.

IF IN THE EYES: Immediately flush with water for at least 20 minutes. Seek medical attention if irritation persists.

IF ON SKIN: Wash affected areas with soap and water. Seek medical attention if irritation persists. Wash contaminated clothing before re-use.

CARCINOGENICITY: None of the ingredients are known/listed carcinogens. However, product may contain trace amounts of inorganic fluorides and crystalline silica. Fluorides have been suggested as a reproductive hazard and a carcinogen. Crystalline silica is listed by IARC as a potential human carcinogen.

SECTION VIII: PRECAUTIONS FOR SAFE HANDLING AND USE

SPILL/RELEASE PROCEDURES: Collect spilled product and store to re-use. Contaminated product and/or environmental media should be recovered and disposed of properly.

WASTE DISPOSAL METHOD: Dispose of in accordance with all federal, state, and local regulations. Reuse recovered product where possible.

HANDLING/STORING PRECAUTIONS: Store in a cool, dry, well ventilated area. Do not store above 120° F. May cause pitting of aluminum.

MSDS ID NO: 45

PREPARED BY: SS

The information and data contained herein is based upon facts considered to be correct as of the date hereof. Information is supplied upon the condition that the persons receiving same will make their own determination as to its suitability for their purposes prior to use. In no event will The Andersons be responsible for damages of any nature whatsoever resulting from the use or reliance upon this information. No representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose or of any other nature are made hereunder with respect to information or the product to which this information refers.