

Supplemental Labeling



Dow AgroSciences LLC

9330 Zionsville Road

Indianapolis, IN 46268-1054 USA

Rodeo[®]

EPA Reg. No. 62719-324

Aerial Application in California Only

ATTENTION

- It is a violation of Federal law to use this product in a manner inconsistent with its labeling.
- This labeling must be in the possession of the user at the time of application.
- Read the label affixed to the container for Rodeo[®] herbicide before applying. Carefully follow all precautionary statements and applicable use directions.
- Use of Rodeo according to this supplemental labeling is subject to all use precautions and limitations imposed by the label affixed to the container for Rodeo.

Directions for Use

Aquatic and Noncrop Sites

When applied as directed and under the conditions described in the "Weeds Controlled" section of the label booklet, this product will control or partially control the labeled weeds growing in the following industrial, recreational, and public areas or other similar sites.

Aquatic Sites: Including all bodies of fresh and brackish water that may be flowing, nonflowing, or transient. This includes lakes, rivers, streams, ponds, seeps, irrigation and drainage ditches, canals, reservoirs, estuaries and similar sites.

If aquatic sites are present in the noncrop area and are part of the intended treatment, read and observe the following directions:

- There is no restriction on the use of treated water for irrigation, recreation, or domestic purposes.
- Consult local and state fish and game agency and water control authorities before applying this product to public water. Permits may be required to treat such water.
- Note: Do not apply this product within 1/2 mile upstream of an active potable water intake in flowing water (i.e., river stream, etc.) or within 1/2 mile of an active potable water intake in a standing body of water such as a lake, pond, or reservoir. To make aquatic applications around and within 1/2 mile of active potable water intakes, the water intake must be turned off for a minimum period of 48 hours after the application. The water intake may be turned on prior to 48 hours if the glyphosate level in the intake water is below 0.7 parts per million as determined by laboratory analysis. These aquatic applications may be made ONLY in those cases where there are alternative water sources or holding ponds that would permit the turning off of an active potable water intake for a minimum period of 48 hours after application.
- This product does not control plants that are completely submerged or have a majority of their foliage under water.

AVOID DRIFT: Do not apply when winds are gusty or under any other condition that will allow drift. Drift may cause damage to any vegetation contacted to which treatment is not intended. To prevent injury to adjacent desirable vegetation, appropriate buffer zones must be maintained.

Aerial Applications

Aerial applications may be made with helicopter only.

Use the following guidelines when aerial applications are made near perennial crops after budbreak and before total leaf drop and/or near emerged annual crops:

1. Do not apply within 100 feet of all desirable vegetation or crop(s).
2. If wind up to 5 miles per hour is blowing toward desirable vegetation or crop(s), do not apply within 500 feet of the desirable vegetation or crop(s).
3. Winds blowing from 5 to 10 miles per hour toward desirable vegetation or crop(s) may require buffer zones in excess of the 500-foot minimum buffer.
4. Do not apply when winds are in excess of 10 miles per hour or when inversion conditions exist.

Coarse sprays are less likely to drift; therefore, do not use nozzles or nozzle configurations that dispense spray as fine spray droplets. Do not angle nozzles forward into the air-stream and do not increase spray volume by increasing nozzle pressure above the manufacturer's recommendation.

Ensure uniform application: To avoid streaking, uneven, or overlapped application, use appropriate marking devices.

Thoroughly wash aircraft, especially landing gear, after each day of spraying to remove residues of this product accumulated during spraying or from spills. **Prolonged exposure of this product to uncoated steel surfaces may result in corrosion and possible failure of the part. Landing gear is most susceptible.** The maintenance of an organic coating (paint) which meets aerospace specification MIL-C-38413 may prevent corrosion.

*Trademark of Dow AgroSciences LLC

D06-077-006
EPA-accepted: 05/15/2002
Initial Printing.