

GRAIN SORGHUM - AT BEDDING

General Information

DIRECTIONS FOR USE

All setbacks must be planted to a crop or seeded with grass or other suitable cover, and all vegetative buffers must be seeded with grass or other suitable cover.

DO NOT load, rinse, or wash equipment within 300 ft from surface water bodies.

DO NOT load, rinse, or wash equipment within 50 ft from wells unless conducted on an impervious surface.

To prevent channeling of surface water runoff, adjust the planter row-cleaners appropriately to prevent rows lower in height than adjacent soil.

Limitations, Restrictions, and Exceptions

GRAIN SORGHUM - AT BEDDING

Application

Knifed-in

Drill granules 1-4 inches below the seed OR 1-4 inches below the seed and up to 5 inches to the side of the seed.

Remarks

DO NOT place granules in direct contact with seed as crop injury may occur.

Only one application of Counter 15G per year may be used.

For any row spacing (minimum 20 inch row spacing) or no more than 11.3 lbs. of Counter 15G per acre.

Method

[N.A.](#)

Rates

[field_rates 0](#)

-

Restricted Entry Interval

48 hours

The 48-hour REI is increased to 72 hours in outdoor areas where average rainfall is less than 25 inches a year.

Exception: If the product is soil-injected or soil-incorporated, the Worker Protection Standard, under certain circumstances, allows workers to enter the treated area if there will be no contact with anything that has been treated.

Timings

[At Bedding](#)