

# **TREE INJECTION TREATMENTS**

## General Information

### GENERAL INFORMATION

Stalker is an aqueous formulation that is readily mixable with water, diesel oil, or recommended seed oils and penetrating oils. Stalker is to be mixed with water or a penetrating oil and applied as a spray to cut stumps and frilling cuts for the control of brush. Stalker should be mixed with a penetrating oil for application to the basal area of brush and trees. Adequate agitation should be maintained with all Stalker emulsion mixtures to prevent phase separation. Prior to actual tank mixing with other products, herbicides and carrier oils, compatibility testing in small containers is recommended!

An application of Stalker is recommended for control of brush in grass pasture and rangeland and noncropland areas such as railroad, utility, highway, and pipeline rights-of-way, utility plant sites, petroleum tank farms, pumping installations, fence rows, storage areas, non-irrigation ditchbanks including grazed or hayed areas within these sites. Stalker is also recommended for use with asphalt and asphalt slurries to control weeds on road shoulders, under pavement, in roadside cracks and crevices, and to prevent weed encroachment on highways and paved surfaces.

Stalker is also recommended for control of undesirable vegetation along forest roads, non-irrigation ditchbanks, and the establishment and maintenance of wildlife openings.

## Limitations, Restrictions, and Exceptions

### TREE INJECTION TREATMENTS

No Worker Protection Standard worker entry restrictions or worker notification requirements apply when this product is directly injected into agricultural plants.

Mix 8.0-12.0 fluid ounces of Stalker in one gallon of water. Using standard injection equipment, apply 1 ml. of Stalker solution at each injection site around the tree with no more than 1 inch intervals between cut edges. Insure that the injector completely penetrates the bark at each site.

Note: Use water as a diluent only when temperatures are sufficient to prevent freezing or add antifreeze (ethylene glycol) according to label directions to prevent freezing.

Method

[Injection](#)

Rates

[field rates 0](#)

- 

Restricted Entry Interval

12 hours

Timings

[N.A.](#)