

RECOMMENDED RATES

General Information

GENERAL INFORMATION:

AMS/2000 is a highly refined and processed spray grade ammonium sulfate/drift reduction agent combination with antifoam included designed to enhance herbicide performance by reducing antagonism in the spray tank, reducing spray drift and increasing deposition of the herbicide for improved uptake by the targeted weed species*.

AMS/2000 disperses rapidly in solution and has been specifically designed to mix well in cold water. AMS/2000 is designed and manufactured for the professional applicator with a very high level of purity to prevent plugged nozzles and screens. It is conveniently packaged and premeasured for a wide range of application rates and equipment.

*Spray drift reduction is dependent on many factors including equipment setup and weather conditions.

For proper management of spray drift and spray deposition, all factors, including the condition and settings of the equipment and wind speed and direction, humidity and temperature must all be taken into account.

DIRECTIONS FOR USE:

Prior to use, read all directions on this label and on the label of the product used.

The product label for specific usages and restrictions have precedence over directions for uses referred to on this label.

MIXING INSTRUCTIONS:

SHAKE WELL OR RECIRCULATE BEFORE USE.

1. Fill sprayer 1/3 to 1/2 full of water
2. Add dry flowables or dispersible granules
3. Add emulsifiable concentrates
4. Continue to agitate until tank is 3/4 full

5. Add AMS/2000 last to the agitating spray tank.

Limitations, Restrictions, and Exceptions

RECOMMENDED RATES:

17 pounds per 100 gallons (2% v/v liquid AMS is equal to 17 pounds of AMS/2000 per 100 gallons of spray solution).

Method

[Spray](#)

Timings

[N.A.](#)