

GROUND AND AERIAL APPLICATION - FOR TRANSLOCATION AND SURFACTANT

General Information

GENERAL INFORMATION:

Fastrack® is a water conditioning and surfactant system that replaces AMS and surfactant for glyphosate tank mixes. The easy-to-use low use rate liquid formulation of Fastrack® is designed to hasten and improve herbicidal uptake. Fastrack® offers superior water conditioning by improving the characteristics of hard water and neutralizing metal cations which can negatively affect performance of certain pesticides. Fastrack® contains surfactants which lower surface tension on the leaf surface and create greater spreading, wetting and penetration of the pesticide into the target plant. Do not use Fastrack® with herbicides that are not compatible in acidic conditions or low pH. Do not use with sulfonyl urea or DSMA based herbicides. Do not use with tank mixes utilizing fixed copper fungicides such as cupric hydroxide, basic copper, copper count N or copper oxychloride.

DIRECTIONS FOR USE:

Prior to use read all directions on this label and on the label of the product used. The product label for specific usages and restrictions have precedence over directions for uses referred to on this label.

MIXING INSTRUCTIONS:

SHAKE WELL OR RECIRCULATE BEFORE USE.

(Recirculate bulk if stored below 32°F)

1. Fill sprayer 1/3 to 1/2 full of water
2. Add Fastrack® to agitating spray tank

3. Add dry flowables or dispersible granules
4. Add emulsifiable concentrates
5. Continue to agitate until tank is full.

Limitations, Restrictions, and Exceptions

General Use Rates (ground and aerial application):

1 quart per 100 gallons (0.25% v/v) for increased translocation and surfactant activity with post-emergent herbicides, fungicides and insecticide sprays. At this rate, additional ammonical nitrogen or water conditioner may be necessary to meet specific label requirements.

Method

[Broadcast/Foliar Air](#)

[Broadcast/Foliar Ground](#)

Rates

[field_rates 0](#)

•

Timings

[N.A.](#)