

REMEDICATION AND RESTORATION SITES - REMEDIAL TREATMENT

General Information

DIRECTIONS FOR USE

SaniDate 5.0 Sanitizer/Disinfectant works best when diluted with water containing minimal levels of organic or inorganic materials, and with water having a neutral pH. Thoroughly rinse out tank with water before mixing concentrate. This product will readily mix with clean, neutral water and does not require agitation.

SaniDate 5.0 Sanitizer/Disinfectant concentrate should not be combined or mixed with any other pesticide concentrates.

This product is not for use on medical device surfaces.

Before use in federally inspected meat and poultry food processing plants and dairies, food products and packaging materials must be removed from room or carefully protected. A potable water rinse is not allowed (Do not rinse) following use of the product as a sanitizer on previously cleaned hard surfaces provided that the surfaces are adequately drained before contact with food so that little or no residue remains.

Limitations, Restrictions, and Exceptions

REMEDICATION AND RESTORATION SITES

SaniDate 5.0 Sanitizer/Disinfectant is recommended for use on hard, non-porous, environmental surfaces such as walls and other hard, nonporous surfaces such as floors, walls, tables, chairs, countertops, garbage bins/cans, bathroom fixtures, sinks, bed frames, shelves, racks, carts, refrigerators (exterior), glazed tile, and use sites listed on the label made of linoleum, vinyl, glazed porcelain, plastic polyethylene, stainless steel, or glass.

Remedial Treatment

SaniDate 5.0 Sanitizer/Disinfectant must be used as part of a comprehensive mold remediation or water damage restoration program, including:

- Periodic monitoring and inspection of conditions favorable to mold growth such as moisture ingress and high relative humidity
- Effective repairs as necessary to eliminate conditions favorable to mold growth
- Drying affected areas to below 20%moisture content

Mix SaniDate 5.0 Sanitizer/Disinfectant at a rate of 0.5 fl. oz. in 1 gallon of water and apply evenly by paintbrush, airless sprayer, low-pressure hand wand, or backpack sprayer. Assure uniform coverage of surfaces to be protected. Surfaces should be evenly wet without runoff or pooling. Permit treated surfaces to be thoroughly dry before painting or affixing overlayment materials such as siding, wallboard, or flooring.

The following associations and internet sites should be consulted for information on standards and guidelines for remedial treatment of mold and mildew:

IAQA-Indoor Air Quality Association (www.iaqa.org)

- EPA-Environmental Protection Agency (www.epa.gov)

- DOH-New York City Department of Health (www.ci.nyc.ny.us/html/doh/html/epi/moldrpt1.html)

- IICRC-Institute of Inspection, Cleaning and Restoration Certification (<http://www.iicrc.org/>)

Method

[Surface](#)

[Spray](#)

Rates

[field_rates 0](#)

•

Timings

[N.A.](#)