

PRE-TREATMENT OF WOOD

General Information

USE INFORMATION

LUM-BOR is a water-soluble inorganic borate salt with insecticidal and fungicidal properties effective against wood-destroying organisms, including the listed target pests. This product can be used for remedial treatment of infested wood, for preventative treatment (before signs of infestations) for wood in existing structures, or for pre-treatment of wood during construction.

This product is recommended for wood and cellulose materials, in accordance with the specific treatment methods described herein. This product is effective for all interior and exterior wood (and wood-foam composite structural components) that will be protected from excessive rain not in direct contact with soil. Types of wood include, but are not limited to, all types of lumber, logs and plywood. This product is toxic to wood-destroying insects, but surface etching of treated wood by target organisms may occur.

Limitations, Restrictions, and Exceptions

PRE-TREATMENT OF WOOD

Spray, foam or powder/dust applications of this product may also be made to wood during construction. Apply solution to all accessible surfaces of bare wood at a rate of approximately 5 gallons per 1,000 square feet of wood surface area. Application should be performed after framing and roofing are in place and before insulation and dry wall are installed. Avoid spraying electrical components. Protect treated wood from excessive rain. End-cuts of wood may also be treated by the application methods listed above or by a 1 to 5 minute dipping in this product's solution.

Do not use as a stand alone preventive treatment for new construction in Florida.

Method

[Spray](#)

[Foam](#)

Rates

[field_rates 0](#)

-

Timings

[N. A.](#)