

# **WOOD TREATMENT - WOOD TREATMENT DURING CONSTRUCTION**

## General Information

### USE INFORMATION

LUM-BOR is a water-soluble inorganic borate salt with insecticidal and fungicidal properties effective against wood-destroying organisms, including the listed target pests. This product can be used for remedial treatment of infested wood, for preventative treatment (before signs of infestations) for wood in existing structures, or for pre-treatment of wood during construction.

This product is recommended for wood and cellulose materials, in accordance with the specific treatment methods described herein. This product is effective for all interior and exterior wood (and wood-foam composite structural components) that will be protected from excessive rain not in direct contact with soil. Types of wood include, but are not limited to, all types of lumber, logs and plywood. This product is toxic to wood-destroying insects, but surface etching of treated wood by target organisms may occur.

## Limitations, Restrictions, and Exceptions

### WOOD TREATMENT

Wood Treatment During Construction: Apply 10 to 25% solution to runoff on all accessible interior and exterior wood surfaces as a minimum treatment to the bottom 24 inches up from foundation or ground at the rate of approximately 5 gallons per 1000 sq. ft.. of wood surface area. Apply after framing and roofing are in place, before insulation and dry wall installed. Treatment may also be made on the whole house.

#### Method

[N. A.](#)

#### Rates

[field rates 0](#)

## field\_rates 1

- 

Timings

After framing and roofing are in place, before insulation and dry wall installed.