

TREATMENT OF PAPER MACHINE WHITE WATER (SHOCK OR INTERMITTENT DOSING)

General Information

DIRECTIONS FOR USE

CONTROL OF ALGAL, FUNGAL, AND BACTERIAL GROWTH IN PULP AND PAPER MILL SYSTEMS FOR FOOD AND NON-FOOD CONTACT PAPER

Proxitane WW -12 provides an effective means to treat various process waters for slime control. Dosage rates should be increased or decreased depending on control achieved.

Maximum usage rate must not exceed 2 lbs Proxitane WW-12 solution per ton (2000 lbs., dry basis) of pulp or paper produced.

Limitations, Restrictions, and Exceptions

TREATMENT OF PAPER MACHINE WHITE WATER

Proxitane WW -12 may be applied within the white water short circulation loop on the paper machine. Apply with either shock, intermittent or continuous dosing. Shock doses may be applied for 1 to 2 hours, as necessary, whereas intermittent doses are applied 1 to 12 times per day, for a duration of 5 to 60 minutes each. For either shock or intermittent dosing, apply 0.02 to 0.8 gallons Proxitane WW -12 per 1000 gallons of white water, producing a peak concentration of 20 to 800 ppm Proxitane WW-12 during dosing. This is approximately equivalent to a peak dose of 2 to 100 ppm 100% peracetic acid.

Method

[N. A.](#)

Rates

[field rates 0](#)

[field rates 1](#)

•

Timings

[N. A.](#)