

# **TREATMENT OF PAPER MACHINE WHITE WATER (CONTINUOUS DOSING)**

General Information

## **DIRECTIONS FOR USE**

### **CONTROL OF ALGAL, FUNGAL, AND BACTERIAL GROWTH IN PULP AND PAPER MILL SYSTEMS FOR FOOD AND NON-FOOD CONTACT PAPER**

Proxitane WW -12 provides an effective means to treat various process waters for slime control. Dosage rates should be increased or decreased depending on control achieved.

Maximum usage rate must not exceed 2 lbs Proxitane WW-12 solution per ton (2000 lbs., dry basis) of pulp or paper produced.

Limitations, Restrictions, and Exceptions

## **TREATMENT OF PAPER MACHINE WHITE WATER**

Proxitane WW -12 may be applied within the white water short circulation loop on the paper machine. Apply with either shock, intermittent or continuous dosing. Shock doses may be applied for 1 to 2 hours, as necessary, whereas intermittent doses are applied 1 to 12 times per day, for a duration of 5 to 60 minutes each. For continuous dosing, apply 0.02 to 0.2 gallons Proxitane WW -12 per 1000 gallons of process water, producing a peak concentration of 20 to 200 ppm of Proxitane WW-12. This is approximately equivalent to 2 to 25 ppm 100% peracetic acid.

Method

[N. A.](#)

Rates

[field\\_rates 0](#)

[field\\_rates 1](#)

•

Timings

[N. A.](#)