

CATALASE CONTROL IN DEINKING WATER LOOPS (SHOCK DOSES)

General Information

DIRECTIONS FOR USE

CONTROL OF ALGAL, FUNGAL, AND BACTERIAL GROWTH IN PULP AND PAPER MILL SYSTEMS FOR FOOD AND NON-FOOD CONTACT PAPER

Proxitane WW -12 provides an effective means to treat various process waters for slime control. Dosage rates should be increased or decreased depending on control achieved.

Maximum usage rate must not exceed 2 lbs Proxitane WW-12 solution per ton (2000 lbs., dry basis) of pulp or paper produced.

Limitations, Restrictions, and Exceptions

CATALASE CONTROL IN DEINKING WATER LOOPS

Proxitane WW-12 may be applied to the inlet lines going to deinking water storage following clarification. Apply with either shock, intermittent, or continuous dosing. Shock doses may be applied for 10 to 60 minutes as necessary. Apply 1.7 to 4.2 gallons Proxitane WW -12 per 1000 gallons recirculation water, producing a peak concentration of 1700 to 4200 ppm Proxitane WW -12 during dosing. This is approximately equivalent to a peak dose of 200 to 500 ppm 100% peracetic acid.

Method

[N. A.](#)

Rates

[field_rates 0](#)

[field_rates 1](#)

-

Timings

[N. A.](#)