

CATALASE CONTROL IN DEINKING WATER LOOPS (CONTINUOUS DOSING)

General Information

DIRECTIONS FOR USE

CONTROL OF ALGAL, FUNGAL, AND BACTERIAL GROWTH IN PULP AND PAPER MILL SYSTEMS FOR FOOD AND NON-FOOD CONTACT PAPER

Proxitane WW -12 provides an effective means to treat various process waters for slime control. Dosage rates should be increased or decreased depending on control achieved.

Maximum usage rate must not exceed 2 lbs Proxitane WW-12 solution per ton (2000 lbs., dry basis) of pulp or paper produced.

Limitations, Restrictions, and Exceptions

CATALASE CONTROL IN DEINKING WATER LOOPS

Proxitane WW-12 may be applied to the inlet lines going to deinking water storage following clarification. Apply with either shock, intermittent, or continuous dosing. Shock doses may be applied for 10 to 60 minutes as necessary. For continuous dosing, apply 0.2 to 1.4 gallons Proxitane WW -12 to 1000 gallons of process water, producing a peak concentration of 200 to 1400 ppm of Proxitane WW -12. This is approximately equivalent to 25 to 170 ppm 100% peracetic acid.

Method

[N. A.](#)

Rates

[field_rates 0](#)

[field_rates 1](#)

-

Timings

[N. A.](#)