

# **NON-FOOD CONTACT PAPER USES: TREATMENT OF CLAYS USED AS COATINGS AND FILLERS ON THE PAPER MACHINE (CONTINUOUS DOSING)**

General Information

DIRECTIONS FOR USE

CONTROL OF ALGAL, FUNGAL, AND BACTERIAL GROWTH IN PULP AND PAPER MILL SYSTEMS FOR FOOD AND NON-FOOD CONTACT PAPER

Proxitane WW -12 provides an effective means to treat various process waters for slime control. Dosage rates should be increased or decreased depending on control achieved.

Maximum usage rate must not exceed 2 lbs Proxitane WW-12 solution per ton (2000 lbs., dry basis) of pulp or paper produced.

Limitations, Restrictions, and Exceptions

CONTROL OF ALGAL, FUNGAL, AND BACTERIAL GROWTH FOR NON-FOOD CONTACT PAPER USES.

TREATMENT OF CLAYS USED AS COATINGS AND FILLERS ON THE PAPER MACHINE - Applications may be made at the recirculation loop or directly to the agitated slurry storage stank. Apply with either shock, intermittent, or continuous dosing. Shock doses may be applied for 1 to 2 hours, as necessary, whereas intermittent doses may be applied for 5 to 60 minutes, 1 to 12 times per day. For continuous dosing applications, apply 0.04 to 0.8 gallons Proxitane® WW -12 to 1000 gallons of process water, producing a peak concentration of 5 to 100 ppm 100% peracetic acid.

Method

[N. A.](#)

Rates

[field\\_rates 0](#)

## field\_rates 1

- 

Timings

N. A.