

NON-FOOD CONTACT PAPER USES: COATINGS PRESERVATION

General Information

DIRECTIONS FOR USE

CONTROL OF ALGAL, FUNGAL, AND BACTERIAL GROWTH IN PULP AND PAPER MILL SYSTEMS FOR FOOD AND NON-FOOD CONTACT PAPER

Proxitane WW -12 provides an effective means to treat various process waters for slime control. Dosage rates should be increased or decreased depending on control achieved.

Maximum usage rate must not exceed 2 lbs Proxitane WW-12 solution per ton (2000 lbs., dry basis) of pulp or paper produced.

Limitations, Restrictions, and Exceptions

CONTROL OF ALGAL, FUNGAL, AND BACTERIAL GROWTH FOR NON-FOOD CONTACT PAPER USES.

COATINGS PRESERVATION - Proxitane WW -12 can be used as an in-container preservative for the control of bacteria and fungi in water-based coatings such as paper coatings. Add 0.1 to 0.7 gallons of Proxitane WW -12 solution to 1,000 gallons of water. This will provide 100 to 700 ppm of Proxitane WW-12, or 12 to 85 ppm 100% peracetic acid.

Method

[N. A.](#)

Rates

[field rates 0](#)

[field rates 1](#)

-

Timings

[N. A.](#)