

NON-FOOD CONTACT PAPER USES: TREATMENT OF DISPERSED PIGMENTS

General Information

DIRECTIONS FOR USE

CONTROL OF ALGAL, FUNGAL, AND BACTERIAL GROWTH IN PULP AND PAPER MILL SYSTEMS FOR FOOD AND NON-FOOD CONTACT PAPER

Proxitane WW -12 provides an effective means to treat various process waters for slime control. Dosage rates should be increased or decreased depending on control achieved.

Maximum usage rate must not exceed 2 lbs Proxitane WW-12 solution per ton (2000 lbs., dry basis) of pulp or paper produced.

Limitations, Restrictions, and Exceptions

CONTROL OF ALGAL, FUNGAL, AND BACTERIAL GROWTH FOR NON-FOOD CONTACT PAPER USES.

TREATMENT OF DISPERSED PIGMENTS -Proxitane WW -12 can be used in the control of bacteria and fungi in the manufacture and storage of dispersed pigments such as kaolin clay, titanium dioxide, calcium carbonate, calcium sulfate, barium sulfate, magnesium silicate and kieselguhr used in paint and paper production. Add 0.12 to 0.6 lb. of Proxitane WW-12 to each 1,000 lbs. of fluid. This will provide 120 to 600 ppm of Proxitane WW-12, or 15 to 70 ppm 100% peracetic acid.

Method

[N. A.](#)

Rates

[field_rates 0](#)

[field_rates 1](#)

•

Timings

[N. A.](#)