

INDOOR CLOSED LOOP, NON-POTABLE, NON-FOOD CONTACT WATER SYSTEMS: TREATMENT OF RAW AND PROCESS WATER (CONTINUOUS DOSING)

General Information

DIRECTIONS FOR USE

CONTROL OF ALGAL, FUNGAL, AND BACTERIAL GROWTH IN PULP AND PAPER MILL SYSTEMS FOR FOOD AND NON-FOOD CONTACT PAPER

Proxitane WW -12 provides an effective means to treat various process waters for slime control. Dosage rates should be increased or decreased depending on control achieved.

Maximum usage rate must not exceed 2 lbs Proxitane WW-12 solution per ton (2000 lbs., dry basis) of pulp or paper produced.

Limitations, Restrictions, and Exceptions

INDOOR CLOSED LOOP, NON-POTABLE, NON-FOOD CONTACT WATER SYSTEMS

TREATMENT OF RAW AND PROCESS WATER (such as heat exchanger system water, boiler water, wet scrubber water, etc) -Proxitane WW -12 may be applied to water at the inlet of the water system or any other suitable point. Apply with either shock, intermittent, or continuous dosing. Shock dosing may be applied for 1 to 2 hours, as necessary, whereas intermittent dosing is applied for 2 to 15 minutes, 4 to 100 times per day. For continuous dosing applications, apply 0.01 to 0.3 gallons Proxitane WW -12 to 1000 gallons of water, producing a peak concentration of 10 to 300 ppm Proxitane WN-12. This is approximately equivalent to 1 to 35 ppm 100% peracetic acid.

Method

[N. A.](#)

Rates

[field_rates 0](#)

field_rates 1

-

Timings

N. A.