

LEAFY VEG (04) - SOIL APPLIED

General Information

PRODUCT INFORMATION

Cotton: A foliar spray of Boll Buster will accelerate opening of mature unopened cotton bolls and enhance defoliation which can result in earlier harvest with an increased recoverable yield. Boll Buster treatment on cotton allows increased efficiency from a once-over harvest.

Tobacco (Flue-Cured): A foliar spray of Boll Buster promotes early, uniform “yellowing” of mature tobacco. Boll Buster reduces curing time, allowing more efficient use of curing barn space, and increased control over harvest schedules.

Spray Preparation

Add 1/2 to 3/4 of the required amount of water to the spray tank. Start agitation. Add the required amount of Boll Buster and the remaining amount of water. Prepare only as much spray solution as can be used on the day of mixing. Do not allow spray solution to stand overnight. Do not spill the concentrated product on spray equipment, or any airplane parts.

ANY SPILLS SHOULD BE RINSED IMMEDIATELY WITH PLENTY OF WATER.

Use of a nurse tank is highly recommended for avoiding possible spills of concentrated formulation on spray equipment or any airplane parts.

Tank Mixtures With Defoliant And Insecticides

Boll Buster is compatible with DFT 6 EC and Malathion. Boll Buster may be applied in sequence or as a tank mixture (DO NOT TANK MIX WITH DESICCANTS IF COTTON IS TO BE SPINDLE HARVESTED). Follow all applicable use precautions and rate per acre recommendations on labels of products applied as tank mixtures or in sequence with Boll Buster. In some cases, slight reduction in boll opening response has been observed when tank mixes with defoliant were used. Good agitation in the spray tank is essential and a tank mixture should not be allowed to stand without agitation for more than 5 to 10 minutes. Read and observe all appropriate label use directions and precautions for the defoliant and insecticides used.

NOTE: UNDER CERTAIN CONDITIONS, TANK MIXTURES OF BOLL BUSTER WITH

DESICCANTS CONTAINING SODIUM CHLORATE COULD RESULT IN THE FORMATION OF HYPOCHLOROUS ACIDS, WHICH ON HEATING WILL EMIT TOXIC CHLORIDE FUMES.

Equipment Cleaning

Because of the acidic nature of Boll Buster, prolonged exposure to spray deposit will damage acrylic plastics, certain paints, and metals.

Rinse thoroughly with a detergent and water all exposed acrylic plastic-type materials (e.g., aircraft windshields), and painted surfaces within an hour after exposure to spray deposits.

At the end of each day, rinse thoroughly with a detergent and water all the metal parts of the aircraft and the associated spray equipment exposed to the spray deposits.

Method

[Band application](#)

[Injection](#)

[Soil application](#)

Timings

[N.A.](#)