

USE WITH ASPHALT AND PAVED SURFACES

General Information

GENERAL INFORMATION

Stalker is an aqueous formulation that is readily mixable with water, diesel oil, or recommended seed oils and penetrating oils. Stalker is to be mixed with water or a penetrating oil and applied as a spray to cut stumps and frilling cuts for the control of brush. Stalker should be mixed with a penetrating oil for application to the basal area of brush and trees. Adequate agitation should be maintained with all Stalker emulsion mixtures to prevent phase separation. Prior to actual tank mixing with other products, herbicides and carrier oils, compatibility testing in small containers is recommended!

An application of Stalker is recommended for control of brush in grass pasture and rangeland and noncropland areas such as railroad, utility, highway, and pipeline rights-of-way, utility plant sites, petroleum tank farms, pumping installations, fence rows, storage areas, non-irrigation ditchbanks including grazed or hayed areas within these sites. Stalker is also recommended for use with asphalt and asphalt slurries to control weeds on road shoulders, under pavement, in roadside cracks and crevices, and to prevent weed encroachment on highways and paved surfaces.

Stalker is also recommended for control of undesirable vegetation along forest roads, non-irrigation ditchbanks, and the establishment and maintenance of wildlife openings.

Limitations, Restrictions, and Exceptions

USE WITH ASPHALT AND PAVED SURFACES

Stalker may be applied at 3 quarts per acre in combination with MC 30, MC 70, RC 70, and SC 70 asphalts to control weeds which encroach on road shoulders under guardrails, or in cracks and crevices of paved surfaces.

The addition of an emulsifier may be needed to allow proper mixing of Stalker with other asphalts. Add Stalker to the distribution tank just before application, allowing sufficient time for it to mix uniformly with the asphalt. Mixtures should not be heated above 150° F. DO NOT allow mixture to stand; apply as soon as thoroughly

mixed.

Method

[N.A.](#)

Rates

[field rates 0](#)

-

Restricted Entry Interval

12 hours

Timings

[N.A.](#)