

WATER CONDITIONING AND DEPOSITION - GROUND

General Information

GENERAL INFORMATION

Bronc Max E.D.T. water conditioning and deposition agent is specially formulated to be used with many postemergence type herbicides, which perform best when mixed with ammonium sulfate. In addition, Bronc Max E.D.T. increases the VMD (Volume Mean Diameter) of the spray droplets and the deposition on the target plant.

Bronc Max E.D.T. is filtered through a special process to remove impurities and other contaminants generally associated with dry or other liquid ammonium sulfate products. This lack of sedimentation reduces nozzle plugging, wear and corrosion of equipment.

Bronc Max E.D.T. contains humectants that retard crystal formation of active ingredients, allowing for better absorption into leaf surfaces.

Limitations, Restrictions, and Exceptions

WATER CONDITIONING and DEPOSITION:

GROUND: Apply at the rate of 2 - 8 pints in 100 gallons of spray (0.25-1% v/v). For best deposition, use 4 - 8 pints per 100 gallons of water (0.5% - 1% v/v).

NOTE: BRONC MAX E.D.T. is a water conditioning and deposition agent. It does not replace the need for an adjuvant or nonionic surfactant. If the spray material label recommends it, then additional adjuvant or nonionic surfactant should be added.

Method

[Broadcast/Foliar Ground](#)

Rates

[field rates 0](#)

[field rates 1](#)

-

Timings

N.A.